



TITAN TUBE

DATASHEET



Optical

Colours
Customized RGGBA

Total LED power
72W

Max. power draw
48W

Emitance (at 1m)
785Lx

TLCI
>96

CRI
>96

Beam Angle
180°

Pixels
16

Electrical

Battery
LG Chem Lithium-Ion

Battery Lifetime
70% after 300 cycles

Battery Runtime
Up to 20 hours

Charging time (nominal)
3 Hours

Input Voltage (Charger)
90-264V 47-63Hz

Input Voltage (Light)
24V, 2A

Control

Backside display
With HSI control

Wireless Modules
865-870MHz | 902-928MHz |
2.4GHz

Range
300m / 330 Yards

DMX
Wired DMX + Wireless (CRMX
&W-DMX)

Construction

Housing
Polycarbonate, metal end caps

IP Rating
IP65















Relative humidity
0-100%

Operating Temperature
0-40 °C
32-104 °F

Weight
1.35kg
3Lbs

Dimensions
Ø42 x 1035mm
Ø1.6" x H40.7"

Accessories

-  **Charger**
FP1-CHR
-  **Eyebolt**
AX1-EBLT (2 pieces Included)
-  **Holder**
AX1-H (2 pieces Included)
-  **Stand**
AX1-STD (Included)
-  **Baby Pin (3/8" & 1/4"-20 threads)**
AX1-BLT
-  **Wing Plate**
AX1-WP (Does not include holders)
-  **Cross Plate**
AX1-CP
-  **Power Box**
FP1-PWB
-  **Charging case**
FP1-CHRCSE
-  **Connection cable**
FP1-PWB-CAB
-  **Snap Box**
SXF44
-  **Snap Bng for 3**
SBAT42
-  **Snap Bng for 1**
SBAT41
-  **Snap Grid**
SGTU14W40